

Laminate Panel 14 Under Carpet Floor Heating

Amuheat's Laminate Panel 14 under carpet floor heating mat is suitable for direct and background heating for both small and large areas.

Low Energy Use & Maintenance Free

Laminate Panel 14 is installed on top of the underlay, directly beneath most modern tufted and woven carpets without impacting floor heights. The thin floor system offers 100% maintenance free operation with low energy usage heat outputs of 60-100W/m² across rooms.

Safety & Construction

Manufactured using only the finest materials, the AS/NZS compliant Teflon insulated heat conductor is sandwiched between layers reinforced aluminium foil laminate with connection to mains earth for complete RCD protection. The highly durable aluminium laminate provides protection for the heating cable and helps to rapidly and evenly distribute heat across the full surface of the mat.




- Purposely designed for under carpet heating applications
- Mat design with a single cold tail for ease of installation
- Over 90% of Laminate Panel 14 consists of metal, primarily Aluminium, which is now considered as a "Green-Metal"
- Certified by Intertek SEMKO against relevant IEC / EN 60335, UL & GOST Standard.



Technical Data

Cable Type	Twin Conductor
Construction	Aluminium foil heater with twin conductor Having primary insulation of FlouroPolymer, sandwiched between 2 layers of specially reinforced aluminium foil
Diameter	2mm
Cold Tail	2500mm
Voltage	230V
Output Power	140W/m ²
Safety	IEC 60335 compliant
Approvals	Intertek SEMKO
Warranty	5 Years

Application Profile



Laminate Panel 14 Strip Range

Code	Length	Watt
LP140-14S	.5 x 2	140
LP210-14S	.5 x 3	210
LP280-14S	.5 x 4	280
LP350-14S	.5 x 5	350
LP420-14S	.5 x 6	420
LP490-14S	.5 x 7	490
LP560-14S	.5 x 8	560
LP630-14S	.5 x 9	630
LP700-14S	.5 x 10	700
LP840-14S	.5 x 12	840
LP980-14S	.5 x 14	980
LP1120-14S	.5 x 16	1120
LP1260-14S	.5 x 18	1260
LP1400-14S	.5 x 20	1400
LP1540-14S	.5 x 22	1540
LP1680-14S	.5 x 24	1680
LP2100-14S	.5 x 30	2100

LP420-14L	1 x 3	420
LP420-14	1.5 x 2	420
LP490-14	1.4 x 2.5	490
LP560-14L	1 x 4	560
LP560-14	2 x 2	560
LP63014R	1.8 x 2.5	630
LP630-14	2.3 x 2	630
LP700-14	2.5 x 2	700
LP840-14	2 x 3	840

Amuheat Pty Limited (Australia) ABN 86133 998 900

Lg1 64 Talavera Road Macquarie Park NSW 2113

Tel: (02) 9114 6934 Fax: (02) 8211 5180

Email: sales@amuheat.com.au

Web: <http://www.amuheat.com.au>